

**4000
SERIES**

4043 4042D
4044 4043D
4045 4044D
4045D

Button expansion modules
for VX2200, VX2300, IPure
and GSM systems

AISI 316 satin steel marine grade*
Vandal resistant IK07



*3 modules installation example with 1 video
speaker unit, 1 module 4044/M and 1 module
4045/M for 9 total push buttons*



*4 modules installation example with
1 video speaker unit, 1 codelock and
2 modules 4045D/M for 20 total push
buttons*



*6 modules installation example with
1 audio speaker unit, 1 information
module and 4 modules 4045D/M for
22 total push buttons*




*9 modules installation example with
1 video speaker unit and 8 modules
4045/M for 42 total push buttons*



100% MADE IN ITALY

Button expansion modules for VX2200, VX2300, IPure and GSM systems

AISI 316 satin steel vandal resistant (IK07)*, blue LED backlit nameplate, IDC connector for connection via flat cable with other optional modules. Operating temperature -20°C to +60°C.

















Reduced installation and maintenance time

All modules of the 4000 series analogue digital call station use flat cables with IDC connectors that allow quick installation, drastically reducing working time, even during maintenance.



Available finishes and versions

		Versions						
		Single button row			Double button row			
Finishes	Anodized aluminium							
		4043/A	4044/A	4045/A	4042D/A	4043D/A	4044D/A	4045D/A
Finishes	Matte finished stainless steel							
		4043D/M	4044D/M	4045D/M	4042D/M	4043D/M	4044D/M	4045D/M

Technical characteristics

	4043	4044	4045	4042D	4043D	4044D	4045D
Buttons	3	4	5	4	6	8	10
Back light	Blue						
IDC connector	Yes						
Button connection terminals	16 pin IDC connector						
Plate type	AISI 316 stainless steel, IK07 vandal resistant*						
Finishes	/M Matte finished stainless steel /A Anodized aluminium						
Mounting	Modular 4000 series - 1 module						
Working voltage	12 Vdc +/- 10%						
Working temperature	-20 +60°C						

* Only for Matte finished stainless steel finish