

4000
SERIES

4384 and 4384X

4000 series buttonless, 1-button or 2-button audio/video module for VX2300 system



4384X-2/M with 1-module wall installation kit 4881

Wide Angle camera

The high-resolution colour camera with wide angle optics allows a wider view.

Visual, voice and acoustic signals

The audio/video modules are equipped with 4 visual signalling LEDs for the deaf: busy, call in progress, communication open and door open. Acoustic signals for the visually impaired indicate a call in progress and busy status.

Extreme durability against weather

All modules are made of AISI316 stainless steel (marine grade) to withstand the weather over time.

Built-in RFID proximity reader*

Allows opening doors with a proximity key, with the possibility of configuring up to 1000 keys.

* Only for 4384X-0, 4384X-1 and 4384X-2

Available finishes and versions

Anodized aluminium



4384-0/A

4384X-0/A

4384-1/A
4384X-1/A

4384-2/A
4384X-2/A

Matte finished stainless steel



4384-0/M

4384X-0/M

4384-1/M
4384X-1/M

4384-2/M
4384X-2/M



100% MADE IN ITALY

4000 series buttonless, 1-button or 2-button audio/video module for VX2300 system

Colour CMOS camera with optional Wide Angle view.

Optional integrated RFID proximity reader for keys (up to 1.000) code 955/T.

AISI316 satin steel, vandal resistant (IK07).

IDC connector for connection via flat cable with other optional modules.

Blue back light name plate.

Status signal LED (Busy/Call in progress/Communication open/Door open).


Configurable programming: Door open/conversation time

Relay: Dry contacts C/NC/NO - 24Vac/dc 2A max or Capacitor discharge (12Vac/dc 1A max).

Telescopic microphone.

Microphone, speaker and balance adjustments.

PTE input, operating temperature -20°C to +60°C.



Reduced installation and maintenance time

All modules of the 4000 series analogue digital call station use flat cables with IDC connectors that allow quick installation, drastically reducing working time, even during maintenance.

Technical characteristics

	4384-0	4384-1	4384-2	4384X-0	4384X-1	4384X-2
Audio/Video	Audio/Video					
Camera and illumination LED's	CMOS 976x582 colour camera White light illumination LED's					
Video signal mode	Modulated					
Wide Camera option	Available (/WD)					
Visual signalling LED	Busy, Ring, Speak, Door Open					
Name plate/Back light	-	Yes/Blue				
Integrated proximity access	-			125Khz H4102 60 keys (via master tag included) 1.000 keys (via PC programming)		
Built-in buttons	0	1	2	0	1	2
Max buttons	40			42		
Programmings	Door time, Conversation time, Door open relay operating mode (capacitor discharge or dry contacts)					
Programming mode	By dip-switch			By dip-switch or by PC		
Interfaces	-			RS-485		
Adjustments	Microphone, Loudspeaker, Balance					
IDC connector	Yes					
PTE input	Yes					
Relay 1	Dry contacts C/NC/NO - 24Vac/dc 2A max or Capacitor discharge (12Vac/dc 1A max)					
Relay 2	SSR C/NO contacts 0.1Amp 50V max					
Finishes	Matte stainless steel (/M), Anodized aluminium (/A)					
Mounting	Modular 4000 series - 1 module					
Power supply	Supplied by the BUS					
Working temperature	-20° / +60°C					

Accessories



4851
1-module flush
installation kit



4881
1-module wall
installation kit




4871
1-module rain shield
with frame for flush
installation kit



4891
1-module rain shield
with frame wall
installation kit



955/T
Blue proximity fob



955/C
White proximity badge
key



VIDEX ELECTRONICS S.P.A.

Via del Lavoro, 1 - 63846 Monte Giberto (FM) - ITALY

tel +39 0734 631669 - fax +39 0734 632475

www.videx.it



Cert. N. IT05/1217