4000 **SERIES**

4842 4842D 4843 4843D 4844 4844D 4845 4845]

Button expansion modules for GSM and traditional systems

AISI 316 satin steel marine grade* Vandal resistant IK07

























3 modules installation example with 1 video speaker unti, 1 module 4844/M and 1 module 4845/M for 9 total push buttons



4 modules installation example with 1 video speaker unit, 1 codelock and 2 modules 4845D/M for 20 total push



6 modules installation example with 1 audio speaker unit, 1 information module and 4 modules 4845D/M for 22 total push buttons




9 modules installation example with 1 video speaker unit and 8 modules 4845/M for 42 total push buttons





Button expansion modules for GSM and traditional systems

AISI 316 satin steel*, blue LED backlit nameplate, vandal resistant (IKO7).



Operating temperature -20°C to +60°C.

Accessories



428

Adapter to connect button expansion modules to VX2200 audio and video speaker untis

438

Adapter to connect button expansion modules to VX2300 audio and video speaker untis

Available finishes

and versions	Versions							
	Single button row				Double button row			
Anodized aluminium								
she	4842/A	4843/A	4844/A	4845/A	4842D/A	4843D/A	4844D/A	4845D/A
Matte finished stainless steel	4842D/M	4843D/M	4844D/M	4845D/M	4842D/M	4843D/M	4844D/M	4845D/M

Technical characteristics

	4842	4843	4844	4845	4842D	4843D	4844D	4845D			
Buttons	2	3	4	5	4	6	8	10			
Name plate	Yes										
Back light	Blue										
Plate type	AISI 316 stainless steel* IK07 vandal resistant										
Plate finishes	/M Matte finished stainless steel /A Anodized aluminium										
Mounting	Modular 4000 series - 1 module										
Button connection terminals	4	6	8	10	8	12	16	20			
Working temperature	-20 +60°C										
Working voltage	12 Vdc +/- 10%										

^{*} Only for Matte finished stainless steel finish

Via del Lavoro, 1 - 63846 Monte Giberto (FM) - ITALY tel +39 0734 631669 - fax +39 0734 632475

www.videx.it

